




























Bandage Polyuréthane coulé dureté 95 ± 3 shore A  
 Corps fonte nervurée pour charges lourdes et extra lourdes  
 Très faible résistance de roulement, silencieuse  
 Grande résistance aux déchirures, aux huiles et aux graisses  
 Température d'emploi : -30°C / + 80°C  
 Moyeu roulements à billes



INDUSTRIEL

					CODE	CODE	CODE	
80	20	12	18	150		870010		
82	28	12	28	220		870020		
82	34	12	34	270		870030		
100	30	15	39	250		870050		
100	40	20	40	300		870070		
125	30	15	39	300		870090		
125	40	20	50	400		870100		
140	60	25	68	700		870120		
150	50	20	50	800		870190		
150	50	20	59	900		870200		
150	50	25	59	800		870210		
175	40	20	49	650		870250		
200	50	20	60	1000		870300		
200	50	25	59	1000		870310		
200	80	30	80	1400		870330		
250	50	25	60	1200		870350		
250	60	25	72.5	1400		870370		
250	80	30	90	1800		870380		
300	70	35	72.5	2200		870410		
300	100	40	50	120	2800		870440	
400	100	40	50	120	3500		870470	
500	100	40	50	120	3700		870530	

Fabrication de toutes dimensions à la demande